

EPAK-CI-2CO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

The analogue converters of the EPAK series are characterised by their compact design. The wide range of functions available with this series of analogue converters make them suitable for applications which do not require international approvals.

Properties:

- Safe isolation, conversion and monitoring of your analogue signals
- Configuration of the input and output parameters directly on the device via DIP switches
- No international approvals
- High interference resistance

General ordering data

Order No.	7760054307
Type	EPAK-CI-2CO
GTIN (EAN)	6944169747731
Qty.	1 pc(s).

EPAK-CI-2CO

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	80 g
------------	------

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-20 °C...60 °C
---------------------	----------------	-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Input

Input current	0...20 mA, 4...20 mA	Input resistance, current	≤ 100 Ω
Input signal	Current source (active) or current sink (passive, 2-wire sensor)	Number of inputs	1

Output

Load impedance current	≤ 300 Ω	Number of outputs	2
Output current	0...20 mA, 4...20 mA		

General data

Accuracy	0.1% FSR	Configuration	none
Galvanic isolation	between input / output / supply	Power consumption	≤ 60mA, 24V supply @ 20mA output, at current source (active sensor), ≤ 80mA, 24V supply @ 20mA output, with 2-wire sensor
Step response time	≤ 500 ms	Temperature coefficient	≤ 300 ppm/K
Type of connection	Screw connection	Voltage supply	20...35 V DC

Insulation coordination

EMC standards	IEC 61326-1	Galvanic isolation	between input / output / supply
Impulse withstand voltage	3 kV (1.2/50μs)	Insulation voltage	1.5 kV _{eff}
Pollution severity	2	Rated voltage	300 V
Surge voltage category	II		

Connection data

Type of connection	Screw connection	Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.6 Nm	Clamping range, rated connection	2 mm ²
Clamping range, min.	0.5 mm ²	Clamping range, max.	2 mm ²
Wire connection cross section AWG, min.	AWG 30	Wire connection cross section AWG, max.	AWG 14

Classifications

ETIM 6.0	EC002653	ETIM 7.0	EC002653
ECLASS 9.0	27-21-01-20	ECLASS 9.1	27-21-01-90
ECLASS 10.0	27-21-01-20	ECLASS 11.0	27-21-01-20

EPAK-CI-2CO

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of
Conformity

[Declaration of Conformity](#)

User Documentation

[Instruction sheet](#)

Brochure/Catalogue

[Catalogues in PDF-format](#)

EPAK-CI-2CO

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

