

PNOZ e8.1p C 24VDC 2so

784198



Safety relay (standalone) Inputs: 1-/2-channel wiring with/without detection of shorts across contacts Outputs: 2 safety outputs, 1 auxiliary output in semiconductor technology UB 24 V DC, width: 22.5 mm, automatic/monitored start. Plug-in terminals of screw type, monitoring E-STOP, safety gates Evaluation device for use with dynamised 2-wire evaluation PLID, only logic OR operation possible.

Datos técnicos

Certificaciones:	CE;cULus Listed;EAC (Eurasian);TÜV
Opciones de aplicación:	Supervisión de parada de emergencia sin retardo;Sensor final de carrera;Supervisor de puertas protectoras
Modos de funcionamiento:	monocanal;Rearme automático;bicanal;Detección de derivación;Comprobación de arranque;Rearme manual con superv.;sin detección de derivación;Autocomprobación;con entrada Y
Estándar de producto:	EN 60947-5-1
Estándares:	DIN V VDE 801-1/A1;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Tensión alimentación (V):	24,0
Tipo de tensión de alimentación:	DC
Tipo de terminal:	Borne de resorte
Salidas de seguridad inst.:	2 ST
Número de salidas de tacto:	1
Categoría de parada:	0
Dimensión Ancho:	22.5 mm
Dimensión de altura:	101.0 mm
Dimensión Profundidad:	121.0 mm
Peso bruto:	145 g
Peso neto:	125 g
Temperatura ambiente:	-10 - 55 °C

Accesorios opcionales



774195

Terminal block filter 1



774196

Terminal block filter 2



774260

PLID d1



784260

PLID d1 C