

## SIHA 3/G20/LD 60-150V

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

### Product image



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### General ordering data

Version	Accessories, Fuse holder, Rated cross-section: Plug-in connection, Wemid, dark beige, Operating instructions/catalogue
Order No.	<a href="#">7921590000</a>
Type	SIHA 3/G20/LD 60-150V
GTIN (EAN)	4032248322626
Qty.	25 pc(s).

Creation date March 29, 2021 10:26:57 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**SIHA 3/G20/LD 60-150V****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	63.1 mm	Depth (inches)	2.484 inch
Height	39.38 mm	Height (inches)	1.55 inch
Net weight	8.48 g	Width	6 mm
Width (inches)	0.236 inch		

**Temperatures**

Operating temperature	-50 °C.../TX]120 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	120 °C		

**Material data**

Material	Wemid	Insulating material	Wemid
Colour	black	UL 94 flammability rating	V-0

**System specifications**

Version	Fuse cartridge	End cover plate required	No
---------	----------------	--------------------------	----

**Additional technical data**

Installation advice	Operating instructions/ catalogue	Type of mounting	Plugged
---------------------	--------------------------------------	------------------	---------

**Conductors for clamping (rated connection)**

Type of connection	Plug-in connection
--------------------	--------------------

**General**

Installation advice	Operating instructions/ catalogue	Operating temperature range, max.	120 °C
---------------------	--------------------------------------	-----------------------------------	--------

**Rating data**

Rated voltage	250 V	Rated impulse withstand voltage	4 kV
Pollution severity	3		

**Classifications**

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-92

**Approvals**

ROHS	Conform
------	---------

**SIHA 3/G20/LD 60-150V****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Downloads**

---

Engineering Data	<a href="#">STEP</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>
Product Change Notification	<a href="#">PCN - EN</a> <a href="#">PCN - DE</a>
User Documentation	<a href="#">Beipackzettel_SIHA3.pdf</a> <a href="#">StorageConditionsTerminalBlocks</a>

---