

**CB 1000/12.5 BLACK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

CB cable ties for the fastening of cables and markers.

- They are particularly suitable for fastening CLI M, SFX, WKM and WKS cable markers
- IEC 62275: 2006-conformant
- Fracture-resistant polyamide PA 6.6 with flammability rating V2 to UL-94

**General ordering data**

|            |                                                                                                                                                                      |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Cable ties, {Reference (AttributeDefinition) not found: pAttr74196859207437}: {Reference (AttributeDefinition) not found: pAttr74196859207437}, Polyamide 66, 1080 N |
| Order No.  | <a href="#">7940006085</a>                                                                                                                                           |
| Type       | CB 1000/12.5 BLACK                                                                                                                                                   |
| GTIN (EAN) | 4032248520343                                                                                                                                                        |
| Qty.       | 50 pc(s).                                                                                                                                                            |

Creation date March 29, 2021 10:30:08 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**CB 1000/12.5 BLACK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 1 mm       | Depth (inches)  | 0.039 inch |
| Height         | 1,000 mm   | Height (inches) | 39.37 inch |
| Net weight     | 25.98 g    | Width           | 12.5 mm    |
| Width (inches) | 0.492 inch |                 |            |

**Temperatures**

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -40...85 °C |
|-----------------------------|-------------|

**Installation materials**

|                                   |         |                                   |              |
|-----------------------------------|---------|-----------------------------------|--------------|
| Cable diameter, max.              | 302 mm  | For re-opening                    | No           |
| Halogen                           | No      | Material                          | Polyamide 66 |
| Operating temperature range, max. | 85 °C   | Operating temperature range, min. | -40 °C       |
| Tensile strength                  | 1,080 N | UL 94 flammability rating         | V-2          |
| UV-resistant                      | No      |                                   |              |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000046    | ETIM 7.0    | EC000046    |
| ECLASS 9.0  | 27-14-07-02 | ECLASS 9.1  | 27-14-07-02 |
| ECLASS 10.0 | 27-14-07-02 | ECLASS 11.0 | 27-14-07-02 |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E317499 |

**Downloads**

|                                             |                                       |
|---------------------------------------------|---------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">DE PI830000160627 002</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>          |

### CB 1000/12.5 BLACK

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

