

QUARTZ TIME SWITCH DAY FORM C 230V/50-60HZ
3 TE AUTOMATIC SU/WI TRANSFER



Model		
product brandname		SETRON
Product designation		Timers
Design of the product		Day
Design of the switching function		CO contact
General technical data		
Manner of function		
• line-synchronous		No
• quartz-controlled		Yes
Shortest switching time interval / of channel 1	min	30
Supply voltage		
Supply voltage frequency		
• minimum	Hz	50
• maximum	Hz	50
Type of voltage / of the supply voltage		AC
Protection class		
Protection class IP		IP20

Switching capacity

Switching capacity current / at AC / at 250 V / Rated value	A	16
---	---	----

Product details

Product feature / floating switching contact		Yes
--	--	-----

Product function

Product function		
• 60 min time program		No
• Automatic daylight-saving adjustment		Yes
• direct operation		Yes
• annual time program		No
• Switching preselection		Yes
• 24-hour time program		Yes
• Weekly time program		No

Number

Number of channels		1
--------------------	--	---

Mechanical Design

Height	mm	83
Width	mm	53
Depth	mm	64
Number of width units		3
Mounting type		DIN rail
Net weight	g	182

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[Umweltbestätigung](#)

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/7LF5301-4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/7LF5301-4/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7LF5301-4

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

