

Diaphragm seal, typ 7MF4920 Flange-type with capillary tube connected to a SITRANS P transmitter for pressure PRESSURE EQUIPMENT DIRECTIVE F GAS 1/LIQUIDS 1 ART. 3.3 SEP process connection flanged acc. EN1092-1/ASME B16.5, Nom. diameter; nom. pressure DN 80; PN 16 to 40 Wetted parts: Tantalum Length of extension tube: none Transmission fluid: silicon oil M5 Length of capillary tube: 2,5 m (8.20 ft) .

Further information

Configurable Products

Technical Data and CAX data (3d-models , eplan.macros) from configurable products cannot shown here. To display the technical data for your device configuration please open PIA LifeCyclePortal and enter there your product number (MLFB). Exemplary 3d-models and eplan-macros are available at the industry imagadatabase. Data for a specific product can be requested with help of a support request.

PIA LifeCyclePortal

<https://pia-portal.automation.siemens.com>

Industry - Image Database

<http://www.automation.siemens.com/bilddb/>

Industry Mall (Online-Order System)

<https://mall.industry.siemens.com>

Information- and Downloadcenter (Catalogs, Brochures, ...)

<http://www.siemens.com/industrial-controls/catalogs>

Support Request

<https://support.industry.siemens.com/my/us/en/requests#createRequest>

last modified:

2/2/2021 