

Pointek CLS300 RF Capacitance point level switch, digital, rod design. Detects level and interface in aggressive liquids, solids, slurries, and foam. Adjustable, 1 m (3.28 ft), insertion, adaptable sensitivity, and active shield to tune out build-up on probe. With display and digital communications. Process Connection: Threaded, 316L (1.4404) stainless steel G 1 1/2"(BSPP), EN ISO 228-1/PF (JIS-P), JIS B 0202 Probe length: (length from flange face) (threaded lengths include process thread) Standard version, rod 350 mm (13.78") Thermal Isolator: With thermal isolator (for process connection temperatures over +85 C (+185 F)) Wetted Seals: FKM Probe Material: 316L Stainless Steel with PFA lining and PEEK Isolators Approvals: General Purpose (CSA, FM, CE, C-TICK) Enclosure and Lid: Aluminum epoxy coated 2 x M20 x 1.5 cable inlet, IP65 Active Shield Length: Standard length - (125 mm threaded, 105 mm flanged)

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

