



Figure similar

FAST LOCK-OUT RELAY 4 CHANGE OVER CONTACTS OPERATING TIME 8MS AUXILIARY VOLTAGE: 60V DC WITH RESET PUSHBUTTON RELAYS WITH SOCKET 7XP9011-1 FOR FLUSH MOUNTING

| General technical data                                   |                       |
|----------------------------------------------------------|-----------------------|
| type of voltage                                          | DC                    |
| continuous current                                       | 10 A                  |
| switching behavior                                       | bistable              |
| type of switching contact                                | bifurcated contact    |
| design of the switching function / positively driven     | Yes                   |
| response time                                            | 10 ms                 |
| Product details                                          |                       |
| product component / LED                                  | No                    |
| Product Functions                                        |                       |
| manual RESET                                             | Yes                   |
| Supply voltage                                           |                       |
| supply voltage / at DC / rated value                     | 60 V                  |
| Inputs / Outputs                                         |                       |
| number of NC contacts                                    | 0                     |
| number of NO contacts                                    | 0                     |
| number of CO contacts                                    | 4                     |
| switching capacity active power / at DC / maximum        | 4 400 W               |
| switching capacity active power / at DC / maximum / note | at 110V DC            |
| Mechanical Design                                        |                       |
| width                                                    | 75 mm                 |
| height                                                   | 80 mm                 |
| depth                                                    | 144.5 mm              |
| type of electrical connection                            | screw-type terminals  |
| product feature / plug-in terminal blocks                | No                    |
| design of the snap-on socket base                        | flush-mounting socket |
| Degree of protection / protection class                  |                       |
| protection class IP / on the front                       | IP40                  |
| protection class IP / rear side                          | IP10                  |
| Environmental conditions                                 |                       |
| ambient temperature / during operation                   | -40 ... +70 °C        |

### Further information

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA2321-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7PA2321-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7PA2321-1](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA2321-1)

**Tender specifications**

<http://www.siemens.com/specifications>

