



Figure similar

FAST LOCK-OUT RELAY 4 CHANGE OVER CONTACTS OPERATING TIME 8MS AUXILIARY VOLTAGE: 30V DC WITH RESET PUSHBUTTON RELAIS WITHOUT SOCKET

General technical data	
type of voltage	DC
continuous current	10 A
switching behavior	bistable
design of the switching function / positively driven	Yes
response time	10 ms
Product details	
product component / LED	No
Product Functions	
manual RESET	Yes
Supply voltage	
supply voltage / at DC / rated value	30 V
Inputs / Outputs	
number of NC contacts	0
number of NO contacts	0
number of CO contacts	4
switching capacity active power / at DC / maximum	4 400 W
switching capacity active power / at DC / maximum / note	at 110V DC
Mechanical Design	
width	45 mm
height	45 mm
depth	108 mm
design of the snap-on socket base	without
Degree of protection / protection class	
protection class IP / on the front	IP40
protection class IP / rear side	IP10
Environmental conditions	
ambient temperature / during operation	-40 ... +70 °C
Further information	

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA2361-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7PA2361-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA2361-0

Tender specifications

<http://www.siemens.com/specifications>

