



Figure similar

Tripping relay 8 changeover contacts Auxiliary voltage: 110/125 V DC  
Tripping time standard, 10 ms Relay without base

| General technical data                                   |                |
|----------------------------------------------------------|----------------|
| type of voltage                                          | DC             |
| continuous current                                       | 10 A           |
| switching behavior                                       | monostable     |
| design of the switching function / positively driven     | Yes            |
| response time                                            | 10 ms          |
| Product details                                          |                |
| product component / LED                                  | No             |
| Product Functions                                        |                |
| manual RESET                                             | No             |
| Supply voltage                                           |                |
| supply voltage / at DC / rated value                     | 125 V          |
| Inputs / Outputs                                         |                |
| number of NC contacts                                    | 0              |
| number of NO contacts                                    | 0              |
| number of CO contacts                                    | 8              |
| switching capacity active power / at DC / maximum        | 4 400 W        |
| switching capacity active power / at DC / maximum / note | at 110V DC     |
| Mechanical Design                                        |                |
| width                                                    | 82.5 mm        |
| height                                                   | 50.4 mm        |
| depth                                                    | 82.5 mm        |
| design of the snap-on socket base                        | without        |
| Degree of protection / protection class                  |                |
| protection class IP / on the front                       | IP40           |
| protection class IP / rear side                          | IP10           |
| Environmental conditions                                 |                |
| ambient temperature / during operation                   | -25 ... +70 °C |
| Further information                                      |                |

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA2632-1AA00-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7PA2632-1AA00-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7PA2632-1AA00-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA2632-1AA00-0)

Tender specifications

<http://www.siemens.com/specifications>

