



Figure similar

Instantaneous relay 4 changeover contacts tripping time 8 ms Auxiliary voltage: 110/125 V DC relay with base 7XP9013-0 for surface-mounting

General technical data	
type of voltage	DC
continuous current	10 A
switching behavior	monostable
type of switching contact	bifurcated contact
design of the switching function / positively driven	Yes
response time	8 ms
Product details	
product component / LED	No
Product Functions	
product function / manual RESET	No
Supply voltage	
supply voltage / at DC / rated value	125 V
Inputs / Outputs	
number of NC contacts	0
number of NO contacts	0
number of CO contacts	4
switching capacity active power / at DC / maximum	4 400 W
switching capacity active power / at DC / maximum / note	at 110V DC
Mechanical Design	
width	48 mm
height	105 mm
depth	104.3 mm
type of electrical connection	screw-type terminals
product feature / plug-in terminal blocks	No
design of the snap-on socket base	surface mounting base
Degree of protection / protection class	
protection class IP / on the front	IP40
protection class IP / rear side	IP10
Environmental conditions	
ambient temperature / during operation	-25 ... +70 °C

Further information

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA2732-0AA00-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7PA2732-0AA00-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA2732-0AA00-2

Tender specifications

<http://www.siemens.com/specifications>

