



Figure similar

Trip circuit supervision relay Single-phase Auxiliary voltage: 110/125 V DC
Relay with base 7XP9011-0 for flush-mounting

General technical data	
type of voltage	DC
continuous current	8 A
switching behavior	monostable
type of switching contact	bifurcated contact
design of the switching function / positively driven	Yes
response time	500 ms
Product details	
product component / LED	No
Product Functions	
manual RESET	No
Supply voltage	
supply voltage / at DC / rated value	125 V
Inputs / Outputs	
number of NC contacts	0
number of NO contacts	2
number of CO contacts	2
switching capacity active power / at DC / maximum	1 650 W
switching capacity active power / at DC / maximum / note	at 110V DC
Mechanical Design	
width	75 mm
height	80 mm
depth	144.5 mm
type of electrical connection	screw-type terminals
design of the snap-on socket base	flush mounting socket
Degree of protection / protection class	
protection class IP / on the front	IP40
protection class IP / rear side	IP10
Environmental conditions	
ambient temperature / during operation	-10 ... +55 °C
Further information	
Information- and Downloadcenter (catalogues, leaflets,...)	
http://www.siemens.com/energy-automation	
Industry Mall (Online ordering system)	
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA3032-1AA00-1	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)	
https://support.industry.siemens.com/cs/ww/en/ps/7PA3032-1AA00-1	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)	
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA3032-1AA00-1	
Tender specifications	

