

Trip circuit supervision relay Three-phase Auxiliary voltage: 220 V
DC Relay without base



General technical data

Type of voltage	DC
Continuous current	8 A
Switching behavior	monostable
Design of the switching function / positively driven	Yes
Response time	500 s

Product details

Product component / LED	No
-------------------------	----

product functions

Product function / Manual RESET	No
---------------------------------	----

Supply voltage

Supply voltage / at DC / Rated value	220 V
--------------------------------------	-------

Inputs / Outputs

Number of NC contacts	0
Number of NO contacts	6
Number of CO contacts	6
Switching capacity active power / at DC / maximum	1 650 W

Mechanical Design

Width	82.5 mm
Height	50.4 mm
Depth	107.1 mm

Degree of protection/protection class

Protection class IP / on the front	IP40
------------------------------------	------

Environmental conditions

Ambient temperature / during operation	-10 ... +55 °C
--	----------------

Further information

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA3042-3AA00-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7PA3042-3AA00-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA3042-3AA00-0

Tender specifications

<http://www.siemens.com/specifications>