



Figure similar

Tripping relay Reyrolle 7PG18, TR-A2-: high burden, EB2 electrical reset contacts, operating coil cut-off: instantaneous, contact arrangement: 10 NO / 10 NC, voltage rating: DC 125 V, back emf suppression diode: not fitted.

General technical data

|                                                                 |      |
|-----------------------------------------------------------------|------|
| type of disconnection / of the exciter winding                  | fast |
| design of the switching contact / contact with automatic reset  | No   |
| design of the switching contact / contact with electrical reset | Yes  |
| design of the switching contact / contact with manual reset     | No   |
| product component / diode                                       | No   |

Supply voltage

|                                         |       |
|-----------------------------------------|-------|
| supply voltage / at DC / rated value    | 125 V |
| type of voltage / of the supply voltage | DC    |

Inputs / Outputs

|                       |    |
|-----------------------|----|
| number of NC contacts | 10 |
| number of NO contacts | 10 |

Further information

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG1823-1LL80-1CF0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7PG1823-1LL80-1CF0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7PG1823-1LL80-1CF0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG1823-1LL80-1CF0)

Tender specifications

<http://www.siemens.com/specifications>

