



Figure similar

RELAY SOLKOR RF CIRCULATING CURRENT/FEEDER PROTECTION IMPROVED DIFFER. CURRENT FEEDER PROTECTION USING PILOT WIRES, FASTER OPERATING TIME, PILOT LOOP RESISTANCE 2000 OHMS MAX. STANDARD INSULATION LEVEL 5KV PILOTS TO EARTH HAND RESET FLAG SELF RESET CONTACTS CONTACT ARRANGEMENT: 3NO/0NC THREE CONTACTS, CASE SIZE E6 (4U HIGH) RATING: 2A AC

General technical data	
Rated current	2 A
Protection Functions	
protection function / 3-pole resolution	Yes
Product function / teleprotection scheme (ANSI 85)	Yes
protection function / differential protection, line (ANSI 87L)	Yes
Supply voltage	
Line frequency	50 ... 60 Hz
Inputs / Outputs	
Number of NC contacts	0
Number of NO contacts	3
Number of digital outputs / incl. signaling contact / maximum	3
Number of current inputs / maximum	3
Mechanical Design	

Width	155 mm
Height	177 mm
Depth	247 mm
Frame size of enclosure	E6

Environmental conditions

Ambient temperature / during operation / maximum	55 °C
--	-------

Further information

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG2111-1DA30-0DC0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7PG2111-1DA30-0DC0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG2111-1DA30-0DC0

Tender specifications

<http://www.siemens.com/specifications>