



5B3 - HIGH IMPRDANCE 50HZ HAND RESET FLAG SELF RESET
CONTACTS CONTACT ARRANGEMENT: 3NO/0NC THREE CONTACTS
SETTING RANGE: 15V AC TO 270V A CASE SIZE E3 (4U HIGH)

Figure similar

Protection Functions	
protection function / three-pole tripping	Yes
protection function / sensitive ground current protection (ANSI 50Ns)	No
protection function / ground fault differential protection (ANSI 87N)	Yes
Supply voltage	
line frequency	50 Hz
Inputs / Outputs	
number of digital outputs / incl. signaling contact / maximum	3
number of current inputs / maximum	1
Mechanical Design	
width	77.5 mm
height	177 mm
depth	216.5 mm
frame size of enclosure	E3
Environmental conditions	
ambient temperature / during operation / maximum	55 °C
Further information	

Information- and Downloadcenter (catalogues, leaflets,...)
<http://www.siemens.com/energy-automation>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG2311-1DA30-1BA0>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/7PG2311-1DA30-1BA0>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG2311-1DA30-1BA0
Tender specifications
<http://www.siemens.com/specifications>

