



Figure similar

Motor protection, Enclosure 1/6 19",4 x I, 3 x U, 3 BI, 5 BO (2 change-over contacts), 1 live contact, 5 temperature sens. Measuring inputs: I_{ph} = 1 A/5 A, I_e= 1 A / 5 A, Rated auxiliary power: 60 to 250 V DC,115 V AC, 230 V AC Installation encl., Screw terminals Region world, IEC / ANSI, English (changeable), Front membrane standard, System interface port B (device underside, rear) Modbus, electrical RS485 without system interf. Port A, Measurement: Fault recording, Functionality: basic version + function package 'HE'

Product details	
number of function keys	9
number of LEDs	8
product functions	
type of measured value detection / of operational measured value / standard	Yes
type of measured value detection / expanded / min./max. values, mean values	No
product function / switching statistics	Yes
product feature / logic editor	Yes
product function / control	Yes
product function / fault recording for analog and digital signals	Yes
product function / monitoring	Yes
number of parameter sets	4
product function / parameter set switchover	Yes
Protection Functions	

protection function / 3-pole resolution	Yes
protection function / with blocked rotor (ANSI 14)	Yes
protection function / undervoltage protection (ANSI 27)	Yes
protection function / directional power monitoring (ANSI 32)	Yes
protection function / undercurrent protection (ANSI 37)	Yes
protection function / temperature monitoring (ANSI 38)	Yes
protection function / unbalance protection (ANSI 46)	Yes
protection function / overcurrent-time protection negative sequence system (ANSI 46)	Yes
protection function / phase-rotation supervision (ANSI 47)	Yes
protection function / overvoltage protection negative-sequence system (ANSI 47)	Yes
protection function / blocked rotor monitoring (ANSI 48)	Yes
protection function / thermal overload protection (ANSI 49)	Yes
protection function / definite-time overcurrent protection (ANSI 50/50N)	Yes
protection function / Switch On To Fault (ANSI SOTF)	Yes
protection function / sensitive ground current protection (ANSI 50Ns)	No
protection function / intermittent ground-fault protection	Yes
protection function / circuit breaker failure protection (ANSI 50BF)	Yes
protection function / inverse-time overcurrent protection (ANSI 51/51N)	Yes
protection function / load step protection (ANSI 50L)	Yes
protection function / dynamic response value changeover (ANSI 51C)	Yes
protection function / voltage-dependent time-overcurrent protection (ANSI 51V)	Yes
product function / power factor (ANSI 55)	Yes
protection function / overvoltage protection (ANSI 59)	Yes
protection function / overvoltage protection zero-sequence system (ANSI 59N)	Yes
protection function / voltage variation protection (ANSI 59R/27R)	Yes
product function / measuring voltage failure detection (ANSI 60FL)	Yes

product function / reclosing lockout (ANSI 66)	Yes
protection function / directional ground fault protection (ANSI 67N)	Yes
protection function / directional sensitive ground-fault detection for resonant-grounded systems and isolated systems (ANSI 67Ns)	Yes
protection function / directional intermittent ground-fault protection	Yes
protection function / trip-circuit supervision (ANSI 74TC)	Yes
protection function / frequency protection (ANSI 81)	Yes
protection function / frequency variation protection (ANSI 81R)	Yes
protection function / closing lock-out (ANSI 86)	Yes
product function / inrush current detection	Yes
protection function / external trip initiation	Yes

Supply voltage

supply voltage / at AC	115 ... 230 V
supply voltage / at DC	60 ... 250 V
type of voltage / of the supply voltage	AC/DC

Inputs / Outputs

number of digital inputs / maximum	3
number of internal RTD inputs / maximum	5
number of digital outputs / incl. signaling contact / maximum	6
number of voltage inputs / maximum	3
number of current inputs / maximum	4
product component / with RTD unit connection	No

Communication

product component / operator interface (on the front)	Yes
software interface version / DIGSI with USB-A port	USB
protocol / is supported / Modbus TCP	No
protocol / is supported / IEC 60870-5-103	No
protocol / is supported / IEC 60870-5-104	No
protocol / is supported / IEC 61850-8-1	No
protocol / is supported / Modbus RTU slave	Yes
protocol / is supported / DNP 3, serial	No
protocol / is supported / DNP 3, TCP	No
protocol / is supported / PROFIBUS DP slave	No
protocol / is supported / PROFINET IO	No
protocol / is supported / PRP	No
protocol / is supported / RSTP	No
protocol / is supported / HSR	No

product function / supports further Ethernet services on Ethernet modules	No
---	----

time synchronization

type of time synchronization	Modbus, pulse via binary input
------------------------------	--------------------------------

Mechanical Design

width	74 mm
height	265.5 mm
depth	228.8 mm
design of the display	Text display: 6 rows
product feature / plug-in terminal blocks	Yes

Environmental conditions

ambient temperature / during operation / maximum	55 °C
--	-------

Further information

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7SK8061-5EB90-1HE0 L0D>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7SK8061-5EB90-1HE0 L0D>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7SK8061-5EB90-1HE0 L0D

Tender specifications

<http://www.siemens.com/specifications>