

FPL 8G1.5/Q8KW/5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Take advantage of our pre-assembled FieldPower® connectors with HQ connectors acc. to IEC 23570 (DESINA) for connecting decentralised motor controller devices quickly and conveniently.

General ordering data

Version	FieldPower®, Cable, Plastic housing, Number of wires: 8, Ölflex Classic 110 8G1.5 or similar, Cross-section: 1.5 mm², 5 m
Order No.	8000005237
Type	FPL 8G1.5/Q8KW/5
GTIN (EAN)	4032248997695
Qty.	1 pc(s).

Creation date March 29, 2021 10:35:56 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

FPL 8G1.5/Q8KW/5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Net weight 1 g

Environmental Product ComplianceREACH SVHC Lead 7439-92-1,
Potassium perfluorobutane
sulfonate 29420-49-3**Technical specifications for cable**

Bending radius, min., moving	159 mm	Bending radius, min., stationary	42,4 mm
Number of wires	8		

General technical data

Protection degree IP65

Classifications

ETIM 6.0	EC001578	ETIM 7.0	EC003250
ECLASS 9.0	27-06-20-11	ECLASS 9.1	27-06-90-90
ECLASS 10.0	27-06-01-06	ECLASS 11.0	27-06-01-06

Approvals

Approvals



ROHS Conform

DownloadsApproval/Certificate/Document of
Conformity [FieldPower](#)

FPL 8G1.5/Q8KW/5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

