

FPL 4G2.5/P/Q4MG/5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Take advantage of our pre-assembled FieldPower® connectors with HQ connectors acc. to IEC 23570 (DESINA) for connecting decentralised motor controller devices quickly and conveniently.

General ordering data

Version	FieldPower®, Cable, Metal housing, Number of wires: 4, Ölflex Classic 110 4G2.5 or similar, Cross-section: 2.5 mm², 5 m
Order No.	8000005295
Type	FPL 4G2.5/P/Q4MG/5
GTIN (EAN)	4032248997619
Qty.	1 pc(s).

FPL 4G2.5/P/Q4MG/5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Net weight	1,147 g
------------	---------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1, Potassium perfluorobutane sulfonate 29420-49-3
------------	--

Technical specifications for cable

Bending radius, min., moving	133.5 mm	Bending radius, min., stationary	35,6 mm
Halogen	Yes	Number of wires	4
Temperature range, moving	-5...70 °C	Temperature range, moving, max.	70 °C
Temperature range, moving, min.	-5 °C	Temperature range, stationary	-40...70 °C
Temperature range, stationary, max.	70 °C	Temperature range, stationary, min.	-40 °C

General technical data

Protection degree	IP65
-------------------	------

Classifications

ETIM 6.0	EC001576	ETIM 7.0	EC001576
ECLASS 9.0	27-06-04-02	ECLASS 9.1	27-06-91-90
ECLASS 10.0	27-06-04-02	ECLASS 11.0	27-06-04-02

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	FieldPower
--	----------------------------

FPL 4G2.5/P/Q4MG/5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

