

BG GHDE 10P REG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The FieldPower® housings are highly robust and meet the highest UL flammability class 5 VA.

- The "TS 35 PT6" mounting rail module and PT6 contact unit are easy to snap on.
- Hinged seals allow pre-assembled plug cables to also be used.
- The high cover versions enable the device to be installed.

For cable seals consult accessories.

General ordering data

Version	Enclosures, IP54, Polycarbonate, GF 10
Order No.	8000007627
Type	BG GHDE 10P REG
GTIN (EAN)	4050118116403
Qty.	1 pc(s).
Available until	2012-09-15

BG GHDE 10P REG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	715 g
------------	-------

Temperatures

Operating temperature	-40 °C...40 °C
-----------------------	----------------

General information #96 connectors

UL 94 flammability rating	5VA
---------------------------	-----

Technical data for equipment installation

Built-in power loss	See project help	Hinged cover insulating material	Polycarbonate
Hinged cover material cover	Transparent	Max. number of REG modules (18 mm) installable	6

Classifications

ETIM 6.0	EC000747	ETIM 7.0	EC000747
ECLASS 9.0	27-18-22-04	ECLASS 9.1	27-18-92-90
ECLASS 10.0	27-18-22-04	ECLASS 11.0	27-18-22-04

Downloads

Approval/Certificate/Document of Conformity	FieldPower
---	----------------------------

BG GHDE 10P REG

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

