

FPL 4G2.5/Q8KW/5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Take advantage of our pre-assembled FieldPower® connectors with HQ connectors acc. to IEC 23570 (DESINA) for connecting decentralised motor controller devices quickly and conveniently.

General ordering data

Version	FieldPower®, Cable, Plastic housing, Number of wires: 4, Ölflex Classic 110 4G2.5 or similar, Cross-section: 2.5 mm ² , 5 m
Order No.	8000011743
Type	FPL 4G2.5/Q8KW/5
GTIN (EAN)	4050118190410
Qty.	1 pc(s).

Creation date March 29, 2021 10:37:17 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

Data sheet

FPL 4G2.5/Q8KW/5

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 893 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1,
 Potassium perfluorobutane
 sulfonate 29420-49-3

Technical specifications for cable

Number of wires 4

General technical data

Protection degree	IP65	Rated current	16 A
Rated voltage	500 V		

Classifications

ETIM 6.0	EC001578	ETIM 7.0	EC003250
ECLASS 9.0	27-06-20-11	ECLASS 9.1	27-06-90-90
ECLASS 10.0	27-06-01-06	ECLASS 11.0	27-06-01-06

Approvals

Approvals



ROHS Conform


FPL 4G2.5/Q8KW/5

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Drawings

Pin assignments



	Pin	Conductor	Assignment
8 - nc	1	1	U
	2	-	-
5 - nc	3	3	W
	4	-	-
PE	5	-	-
	6	-	-
3 - W	7	2	V
	8	-	-
2 - nc	PE	gr./yell.	PE