

FP PRO TOP1 24/20 3M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

PROtop power supplies offer a wide range of functions with many advantages. These include high energy efficiency, outstanding power reserves, high reliability, and optional communication capability. Thanks to the possibility of integrating our PROtop power supplies into the FieldPower® system, the entire range of functions can be made available in the field – with all the advantages of the FieldPower® modular system.

Allgemeine Bestelldaten

Best.-Nr.	8000051705
Typ	FP PRO TOP1 24/20 3M
GTIN (EAN)	4050118770735
VPE	1 Stück
Referenzprodukt	2466890000

FP PRO TOP1 24/20 3M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technische Daten

Abmessungen und Gewichte

Breite	284 mm	Breite (inch)	11,181 inch
Höhe	196 mm	Höhe (inch)	7,717 inch
Nettogewicht	5.841 g	Tiefe	220 mm
Tiefe (inch)	8,661 inch		

Temperaturen

Lagertemperatur	-40 °C...85 °C	Umgebungstemperatur	-25 °C...+50 °C
Betriebstemperatur	-25 °C...		

Umweltanforderungen

REACH SVHC	Lead 7439-92-1
------------	----------------

Eingang

Nenneingangsspannung	100 - 240 V AC / 120 - 340 V DC	Einschaltstrom	max. 5 A
Eingangssicherung (intern)	Ja		

Ausgang

Nennausgangsspannung	24 V DC $\pm$ 1 %	Nennausgangsstrom @ U _{Nenn}	20 A @ 40 °C
----------------------	-------------------	---------------------------------------	--------------

Allgemeine Angaben

Betriebstemperatur	-25 °C...	Einbauhinweis	Schrauben beiliegend
--------------------	-----------	---------------	----------------------

Klassifikationen

ETIM 6.0	EC000214	ETIM 7.0	EC000214
ECLASS 9.0	27-14-24-09	ECLASS 9.1	27-14-24-09
ECLASS 10.0	27-14-24-09	ECLASS 11.0	27-14-24-09

Wichtiger Hinweis

Produkthinweis	Please find the parts list under individual parts. Enclosure seals have to be ordered separately. You find them under accessories.
----------------	--

Zulassungen

ROHS	Konform
------	---------

Downloads

Broschüre/Katalog	Catalogues in PDF-format
-------------------	--

FP PRO TOP1 24/20 3M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Zeichnungen

