

Connecting cable NEBV-

Part number: 8003577

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Additional functions	Holding current reduction Protective circuit
Cable designation	Without label holder
Contact durability	50
Electrical connection 1, function	Field device end
Electrical connection 1, design	Rectangular
Electrical connection 1, connection type	Socket Socket, narrow
Electrical connection 1, cable outlet	Straight Angled
Electrical connection 1, connection technology	Connection diagram ZC, self-tapping screw Connection diagram ZC, metric screw Connection diagram type C as per EN 175301-803 Sub-D
Electrical connection 1, number of pins/wires	25
Electrical connection 2, function	Control side
Electrical connection 2, design	Rectangular Round
Electrical connection 2, connection type	Cable Plug
Electrical connection 2, cable outlet	Straight Angled
Electrical connection 2, connection technology	Connection diagram ZB, self-tapping screw M8x1 A-coded as per EN 61076-2-104 Open end
Electrical connection 2, number of pins/wires	3
DC operating voltage range	0 V ... 230 V
Operating voltage range AC	0 V ... 230 V
Cable length	0.5 m ... 30 m
Cable characteristic	Standard Suitable for energy chains
Connector cable test conditions	Test conditions on request
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions To UK instructions for electrical equipment
LABS (PWIS) conformity	VDMA24364-B2-L

Feature	Value
Note on materials	RoHS-compliant
Material of cable sheath	PVC TPE-U(PUR)
Color cable sheath	Gray