


Manifold sub-base VABV-S1-1SB-N38

FESTO

Part number: 8029813



 [General operating condition](#)

Data sheet

| Feature | Value |
|--|--|
| Width | 44 mm |
| Exhaust air function | With flow control option |
| Based on norm | ISO 5599-1 |
| Max. no. of valve positions | 1 |
| Operating pressure | -0.09 MPa ... 1.6 MPa |
| Operating pressure | -0.9 bar ... 16 bar |
| Suitability for vacuum | yes |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | -20 °C ... 60 °C |
| Temperature of medium | -10 °C ... 50 °C |
| Pilot medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Ambient temperature | -10 °C ... 50 °C |
| Product weight | 490 g |
| Pneumatic connection 2 | 3/8 NPT |
| Pneumatic connection 4 | 3/8 NPT |
| Note on materials | RoHS-compliant |
| Material of sub-base | Die-cast aluminum |