



# Air solenoid valve VSVA-B-P53ED-ZTR-A2-1T1L

Part number: 8039181

**FESTO**



[General operating condition](#)

## Data sheet

| Feature                                                                 | Value                                                                     |
|-------------------------------------------------------------------------|---------------------------------------------------------------------------|
| Valve function                                                          | 5/3, exhausted                                                            |
| Actuation type                                                          | Electrical                                                                |
| Width                                                                   | 18 mm                                                                     |
| Standard nominal flow rate                                              | 380 l/min                                                                 |
| Pneumatic working port                                                  | Sub-base, size 18 mm as per ISO 15407-1<br>G1/8                           |
| Operating voltage                                                       | 24V DC                                                                    |
| Operating pressure                                                      | -0.09 MPa ... 1 MPa                                                       |
| Operating pressure                                                      | -0.9 bar ... 10 bar                                                       |
| Structural design                                                       | Piston gate valve                                                         |
| Reset method                                                            | Mechanical spring<br>Electrical actuation                                 |
| Degree of protection                                                    | IP65<br>NEMA 4                                                            |
| Nominal width                                                           | 5 mm                                                                      |
| Exhaust air function                                                    | With flow control option<br>Via throttle plate<br>Via individual sub-base |
| Sealing principle                                                       | Soft                                                                      |
| Mounting position                                                       | Any                                                                       |
| Manual override                                                         | Detenting via accessory<br>Non-detenting                                  |
| Type of control                                                         | Pilot-controlled                                                          |
| Pilot air supply port                                                   | External                                                                  |
| Flow direction                                                          | Non-reversible                                                            |
| Symbol                                                                  | 00992824                                                                  |
| Lap                                                                     | Overlap                                                                   |
| Signal status display                                                   | LED                                                                       |
| Pilot pressure MPa                                                      | 0.3 MPa ... 1 MPa                                                         |
| Pilot pressure                                                          | 3 bar ... 10 bar                                                          |
| Flow rate of pneumatic valve on individual sub-base                     | 390 l/min                                                                 |
| Optimized flow rate of pneumatic valve, pneumatically concatenated flow | 430 l/min                                                                 |
| Optimized flow rate of pneumatic valve pneumatically concatenated flow  | 380 l/min                                                                 |
| Asymmetrical switching time off                                         | 37 ms for control side 12                                                 |
| Asymmetrical switching time on                                          | 10 ms for control side 14<br>13 ms for control side 12                    |
| Duty cycle                                                              | 100%                                                                      |

| Feature                                   | Value                                                                                |
|-------------------------------------------|--------------------------------------------------------------------------------------|
| Max. positive test pulse with 0 signal    | 1500 µs                                                                              |
| Max. negative test pulse on 1 signal      | 800 µs                                                                               |
| Nominal operating voltage DC              | 24 V                                                                                 |
| Coil characteristics                      | 24 V DC: 1.6 W                                                                       |
| Surge resistance                          | 2.5 kV                                                                               |
| Contamination level                       | 3                                                                                    |
| Permissible voltage fluctuations          | +/- 10 %                                                                             |
| Operating medium                          | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Information on operating and pilot media  | Operation with oil lubrication possible (required for further use)                   |
| Vibration resistance                      | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance                          | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27                |
| Corrosion resistance class (CRC)          | 0 - No corrosion stress                                                              |
| LABS (PWIS) conformity                    | VDMA24364-B1/B2-L                                                                    |
| Temperature of medium                     | -5 °C ... 50 °C                                                                      |
| Relative air humidity                     | 0 - 90 %                                                                             |
| Noise level                               | 85 dB(A)                                                                             |
| Ambient temperature                       | -5 °C ... 50 °C                                                                      |
| Max. tightening torque for valve mounting | 0.8 Nm ... 1.2 Nm                                                                    |
| Product weight                            | 170 g                                                                                |
| Electrical connection                     | 4-pin<br>Plug<br>as per ISO 15407-2                                                  |
| Type of mounting                          | On sub-base                                                                          |
| Pilot air port 12/14                      | Sub-base, size 18 mm as per ISO 15407-2                                              |
| Pilot exhaust air port 82/84              | Ducted<br>Not ducted<br>Optionally:                                                  |
| Pneumatic connection 1                    | Sub-base, size 18 mm as per ISO 15407-2                                              |
| Pneumatic connection 2                    | Sub-base, size 18 mm as per ISO 15407-2                                              |
| Pneumatic connection 3                    | Sub-base, size 18 mm as per ISO 15407-2                                              |
| Pneumatic connection 4                    | Sub-base, size 18 mm as per ISO 15407-2                                              |
| Pneumatic connection 5                    | Sub-base, size 18 mm as per ISO 15407-2                                              |
| Note on materials                         | RoHS-compliant                                                                       |
| Seals material                            | FPM<br>NBR                                                                           |
| Housing material                          | Die-cast aluminum<br>PA                                                              |
| Material of screws                        | Steel, galvanized                                                                    |