

# Manifold block VABS-P4-20S-G38

Part number: 8087328

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                  | Value                                                                      |
|------------------------------------------|----------------------------------------------------------------------------|
| Width                                    | 25 mm                                                                      |
| Mounting position                        | Any                                                                        |
| Structural design                        | Connection direction at side                                               |
| Max. no. of valve positions              | 1                                                                          |
| Operating pressure                       | 0 bar ... 7 bar                                                            |
| Operating medium                         | Inert gas<br>Air                                                           |
| Information on operating and pilot media | Operation with oil lubrication not possible<br>Maximum particle size 10 µm |
| Corrosion resistance class (CRC)         | 2 - Moderate corrosion stress                                              |
| LABS (PWIS) conformity                   | VDMA24364 zone III                                                         |
| Storage temperature                      | -40 °C ... 80 °C                                                           |
| Temperature of medium                    | 5 °C ... 50 °C                                                             |
| Ambient temperature                      | 5 °C ... 50 °C                                                             |
| Product weight                           | 97 g                                                                       |
| Type of mounting                         | With through-hole                                                          |
| Pneumatic connection 1                   | G3/8                                                                       |
| Pneumatic connection 2                   | G3/8                                                                       |
| Note on materials                        | RoHS-compliant                                                             |
| Material of sub-base                     | Wrought aluminum alloy, anodized                                           |