


# Solenoid valve VSNC-FT-B52-N14-P2

Part number: 8114699

FESTO



General operating condition

## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Valve function                           | 5/2, bistable                                                      |
| Actuation type                           | Electrical                                                         |
| Width                                    | 32 mm                                                              |
| Standard nominal flow rate               | 1000 l/min                                                         |
| Pneumatic working port                   | NAMUR connection diagram                                           |
| Operating voltage                        | Via solenoid coil, to be ordered separately                        |
| Operating pressure                       | 0.15 MPa ... 0.8 MPa                                               |
| Operating pressure                       | 1.5 bar ... 8 bar                                                  |
| Structural design                        | Plate seat                                                         |
| Exhaust air function                     | With flow control option                                           |
| Sealing principle                        | Soft                                                               |
| Mounting position                        | Any                                                                |
| Conforms to standard                     | VDI/VDE 3845 (NAMUR)                                               |
| Manual override                          | None                                                               |
| Type of control                          | Pilot-controlled                                                   |
| Pilot air supply port                    | Internal                                                           |
| Flow direction                           | Non-reversible                                                     |
| Symbol                                   | 00991953                                                           |
| Lap                                      | Underlap                                                           |
| Changeover time                          | 2 ms                                                               |
| Duty cycle                               | 100%                                                               |
| Coil characteristics                     | See solenoid coil, to be ordered separately                        |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                   | VDMA24364-B2-L                                                     |
| Temperature of medium                    | -20 °C ... 60 °C                                                   |
| Ambient temperature                      | -20 °C ... 60 °C                                                   |
| Product weight                           | 422 g                                                              |
| Type of mounting                         | With through-hole                                                  |
| Venting hole connection                  | Not ducted                                                         |
| Pneumatic connection 1                   | 1/4 NPT                                                            |
| Pneumatic connection 2                   | NAMUR connection diagram                                           |
| Pneumatic connection 3                   | 1/4 NPT                                                            |
| Pneumatic connection 4                   | NAMUR connection diagram                                           |
| Pneumatic connection 5                   | 1/4 NPT                                                            |

| Feature            | Value                  |
|--------------------|------------------------|
| Note on materials  | RoHS-compliant         |
| Seals material     | NBR                    |
| Housing material   | Wrought aluminum alloy |
| Material of screws | Steel, galvanized      |