


Parallel gripper DHPC-...-40-A-

Part number: 8116734

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Size	40
Stroke per gripper jaw	15 mm
Max. interchangeability	0.2 mm
Max. gripper jaw angular play ax, ay	0 deg
Max. gripper jaw backlash Sz	0 mm
Rotational symmetry	≤0.2 mm
Pneumatic gripper repetition accuracy	≤0.02 mm
Number of gripper jaws	2
Actuator system	Pneumatic
Mounting position	Any
Mode of operation	Double-acting Single-acting Closed Open
Gripper function	Parallel
Gripping force backup	Without
Structural design	Positively driven motion sequence
Guide	Ball guide
Position sensing	For proximity sensor
Symbol	00991894 00997348 00997349
Operating pressure	0.1 MPa ... 0.8 MPa
Operating pressure	1 bar ... 8 bar
Operating pressure	14.5 psi ... 116 psi
Max. operating frequency of pneumatic gripper	1 Hz
Min. opening time at 6 bar	158 ms ... 370 ms
Min. closing time at 6 bar	67 ms ... 153 ms
Max. mass per external gripper finger	400 g
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	0 - No corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Ambient temperature	-10 °C ... 60 °C
Gripping force per gripper jaw at 6 bar, opening	733.5 N ... 777.2 N

Feature	Value
Gripping force per gripper jaw at 6 bar, closing	675 N ... 717.2 N
Gripping force per gripper jaw at 6 bar, opening	366.8 N ... 388.6 N
Gripping force per gripper jaw at 6 bar, closing	337.5 N ... 358.6 N
Mass moment of inertia	14.87 kgcm ² ... 17.06 kgcm ²
Maximum force on gripper jaw F _z , static	351.5 N
Maximum torque on gripper jaw, M _x static	16.15 Nm
Maximum torque on gripper jaw, M _y static	9.55 Nm
Maximum torque on gripper jaw, M _z static	9.55 Nm
Product weight	1396 g ... 1740 g
Type of mounting	With through-hole and dowel pin With internal thread and dowel pin
Pneumatic connection	M5
Note on materials	RoHS-compliant
Housing material	Aluminum, anodized
Gripper jaw material	High-alloy stainless steel