

# Parallel gripper DHPC-6-A-NO-S

Part number: 8116741

FESTO



 General operating condition

## Data sheet

| Feature                                            | Value                                                                                                                                                                                                                          |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                               | 6                                                                                                                                                                                                                              |
| Stroke per gripper jaw                             | 2 mm                                                                                                                                                                                                                           |
| Max. interchangeability                            | 0.2 mm                                                                                                                                                                                                                         |
| Max. gripper jaw angular play ax, ay               | 0 deg                                                                                                                                                                                                                          |
| Max. gripper jaw backlash Sz                       | 0 mm                                                                                                                                                                                                                           |
| Rotational symmetry                                | ≤0.2 mm                                                                                                                                                                                                                        |
| Pneumatic gripper repetition accuracy              | ≤0.02 mm                                                                                                                                                                                                                       |
| Number of gripper jaws                             | 2                                                                                                                                                                                                                              |
| Actuator system                                    | Pneumatic                                                                                                                                                                                                                      |
| Mounting position                                  | Any                                                                                                                                                                                                                            |
| Mode of operation                                  | Single-acting<br>Open                                                                                                                                                                                                          |
| Gripper function                                   | Parallel                                                                                                                                                                                                                       |
| Gripping force backup                              | On opening                                                                                                                                                                                                                     |
| Structural design                                  | Positively driven motion sequence                                                                                                                                                                                              |
| Guide                                              | Ball guide                                                                                                                                                                                                                     |
| Position sensing                                   | For proximity sensor                                                                                                                                                                                                           |
| Symbol                                             | 00997349                                                                                                                                                                                                                       |
| Variants                                           | Metals with copper, zinc or nickel by mass as main constituent are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils. |
| Operating pressure                                 | 0.35 MPa ... 0.8 MPa                                                                                                                                                                                                           |
| Operating pressure                                 | 3.5 bar ... 8 bar                                                                                                                                                                                                              |
| Operating pressure                                 | 50.75 psi ... 116 psi                                                                                                                                                                                                          |
| Max. operating frequency of pneumatic gripper      | 3 Hz                                                                                                                                                                                                                           |
| Min. opening time at 6 bar                         | 16 ms                                                                                                                                                                                                                          |
| Min. closing time at 6 bar                         | 16 ms                                                                                                                                                                                                                          |
| Max. mass per external gripper finger              | 6 g                                                                                                                                                                                                                            |
| Operating medium                                   | Compressed air as per ISO 8573-1:2010 [7:4:4]                                                                                                                                                                                  |
| Information on operating and pilot media           | Operation with oil lubrication possible (required for further use)                                                                                                                                                             |
| Corrosion resistance class (CRC)                   | 0 - No corrosion stress                                                                                                                                                                                                        |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                                                                                                                                                                                 |
| Suitability for the production of Li-ion batteries | Suitable for battery production with reduced Cu/Zn/Ni values (F1a)                                                                                                                                                             |
| Ambient temperature                                | -10 °C ... 60 °C                                                                                                                                                                                                               |
| Gripping force per gripper jaw at 6 bar, closing   | 7.8 N                                                                                                                                                                                                                          |

| Feature                                          | Value                                                                          |
|--------------------------------------------------|--------------------------------------------------------------------------------|
| Gripping force per gripper jaw at 6 bar, closing | 3.9 N                                                                          |
| Mass moment of inertia                           | 0.012 kgcm <sup>2</sup>                                                        |
| Maximum force on gripper jaw Fz, static          | 22 N                                                                           |
| Maximum torque on gripper jaw, Mx static         | 0.24 Nm                                                                        |
| Maximum torque on gripper jaw, My static         | 0.11 Nm                                                                        |
| Maximum torque on gripper jaw, Mz static         | 0.11 Nm                                                                        |
| Product weight                                   | 27 g                                                                           |
| Type of mounting                                 | Optionally:<br>Direct mounting via through-hole<br>Direct fastening via thread |
| Pneumatic connection                             | M3                                                                             |
| Note on materials                                | RoHS-compliant                                                                 |
| Housing material                                 | Aluminum, anodized                                                             |
| Gripper jaw material                             | High-alloy stainless steel                                                     |