


Twin cylinder DGTZ-GF-16- -J-T-P-A

Part number: 8150887

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Min. stroke limit (hard)	101 mm
Stroke	101 mm ... 200 mm
Max. stroke limit (hard)	200 mm
Adjustable end position range/length	10 mm
Piston diameter	16 mm
Drive unit operating mode	Two yokes
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Guide	Sliding guide
Structural design	Guide
Position sensing	For proximity sensor
Symbol	00991243
Operating pressure	0.12 MPa ... 0.8 MPa
Operating pressure	1.2 bar ... 8 bar
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Cleanroom class	Class 5 according to ISO 14644-1
Ambient temperature	-10 °C ... 80 °C
Impact energy in the end positions	0.15 J
Max. payload as a function of the stroke at defined distance xs	10.7 N ... 11.3 N
Theoretical force at 6 bar, retracting	181 N
Theoretical force at 6 bar, advancing	181 N
Moving mass	293 g ... 453 g
Moving mass at 0 mm stroke	133 g
Additional moving mass per 10 mm stroke	16 g
Product weight	767 g ... 1070 g
Basic weight with 0 mm stroke	370 g
Additional weight per 10 mm stroke	35 g
Pneumatic connection	M5
Note on materials	RoHS-compliant
Cover material	Wrought aluminum alloy
Seals material	NBR

Feature	Value
Housing material	Wrought aluminum alloy, anodized
Piston rod material	High-alloy stainless steel