

# Connection kit DADG-AK-G8-16-20

Part number: 8152381

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                        | Value                                         |
|------------------------------------------------|-----------------------------------------------|
| Size                                           | 16                                            |
| Stroke                                         | 20 mm                                         |
| Operating pressure                             | 0.1 MPa ... 0.8 MPa                           |
| Operating pressure                             | 1 bar ... 8 bar                               |
| Operating pressure                             | 14.5 psi ... 116 psi                          |
| Operating medium                               | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Corrosion resistance class (CRC)               | 1 - Low corrosion stress                      |
| LABS (PWIS) conformity                         | VDMA24364-B1/B2-L                             |
| Ambient temperature                            | -10 °C ... 60 °C                              |
| Max. tightening torque                         | 1.5 Nm                                        |
| Tightening torque tolerance                    | ±10%                                          |
| Max. tightening torque, pneumatic connection 1 | 0.7 Nm                                        |
| Product weight                                 | 13.5 g                                        |
| Pneumatic connection                           | M5                                            |
| Adapter material                               | Epoxy resin                                   |
| Seals material                                 | NBR                                           |
| Material of screws                             | Steel, coated                                 |