



Vacuum generator OVPN-23-L3-PG14-G34-UA

Part number: 8199148

FESTO



 [General operating condition](#)

Data sheet

Feature	Value
Nominal width of Laval nozzle	2.3 mm
Width dimension	60 mm
Muffler construction type	Open
Mounting position	Any
Ejector characteristics	High suction rate
Integrated function	Pneumatic muffler open
Structural design	Vacuum generator 3-stage
Symbol	00991489
Operating pressure for max. suction rate	0.8 MPa
Operating pressure for max. suction rate	8 bar
Operating pressure for max. suction rate	116 psi
Operating pressure	0.1 MPa ... 0.8 MPa
Operating pressure	1 bar ... 8 bar
Operating pressure	14.5 psi ... 116 psi
Operating pressure for max. vacuum	0.79 MPa
Operating pressure for max. vacuum	7.9 bar
Operating pressure for max. vacuum	114.55 psi
Max. vacuum	81 %
Nominal operating pressure	0.6 MPa
Nominal operating pressure	6 bar
Nominal operating pressure	87 psi
Max. suction rate with respect to atmosphere	748 l/min
Air supply time at nominal operating pressure	0.13 s
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication not possible
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Temperature of medium	0 °C ... 60 °C
Cleaning advice	Soap suds (except silencers)
Noise level at nominal operating pressure	72 dB(A)
Ambient temperature	0 °C ... 60 °C
Product weight	940 g
Type of mounting	Direct mounting via through-hole With mounting bracket
Pneumatic connection 1	G1/4

Feature	Value
Pneumatic connection 3	Pneumatic muffler open
Vacuum connection	G3/4
Material of connecting thread	POM
Seals material	NBR
Female nozzle material	PA-reinforced
Housing material	POM
Muffler material	PA-reinforced PU foam
Material of screws	High-alloy stainless steel
Material of jet nozzle	PA-reinforced