


MCZ SC 0-20MA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****MCZ: The smallest solution**

- The smallest analogue signal converter in terminal block format on the market
- Space-saving conversion of analogue signals in the control cabinet thanks to the slim, 6 mm wide module width
- Simple wiring with plug-in cross-connectors

General ordering data

Version	Limit value monitoring, Input : 0-20 mA, Output 2 x transistor
Order No.	8227350000
Type	MCZ SC 0-20MA
GTIN (EAN)	4008190193799
Qty.	10 pc(s).

MCZ SC 0-20MA

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	63.2 mm	Depth (inches)	2.488 inch
Length	91 mm	Length (inches)	3.583 inch
Net weight	28 g	Weight	30 g
Width	6 mm	Width (inches)	0.236 inch

Temperatures

Storage temperature	-25 °C...60 °C	Operating temperature	0 °C...50 °C
Humidity	40 °C / 93 % rel. humidity, no condensation		

Probability of failure

MTTF	681 Years
------	-----------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Input

Input current	0.5...20 mA	Input resistance, current	50 Ω
Number of inputs	1	Voltage drop	1 V

Output

Contact assembly	Transistor output, double switch output PNP	Cut-off frequency (-3 dB)	100 Hz
Number of outputs	2	Switching thresholds	Via 2 potentiometers (12 turns)

General data

Configuration	Potentiometer	Current consumption	15 mA
Galvanic isolation	Without isolation	Rail	TS 35
Step response time	< 250 µs (switching threshold at 90% of max. input signal; $R_i \leq 1$ kΩ)	Temperature coefficient	max. 250 ppm/K
Type of connection	Tension-clamp connection	Voltage supply	24 V DC $\pm$ 20 %

Insulation coordination

EMC standards	EN 55011, EN 61000-6	Galvanic isolation	Without isolation
Insulation voltage input or output/rail	4 kV _{eff} / 1 min.		

Connection data

Type of connection	Tension-clamp connection	Clamping range, rated connection	1.5 mm ²
Clamping range, min.	0.5 mm ²	Clamping range, max.	1.5 mm ²

MCZ SC 0-20MA

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC002654	ETIM 7.0	EC002654
ECLASS 9.0	27-21-01-22	ECLASS 9.1	27-21-01-22
ECLASS 10.0	27-21-01-22	ECLASS 11.0	27-21-01-22

Tender specification sheets

Long specification

Short specification

Trip amplifier for monitoring a 0...20 mA standard signal with two switching outputs

Trip amplifier in 6 mm width for analogue 0...20 mA standard signals with two PNP-transistor switch outputs for monitoring an upper and lower threshold (adjustable via potentiometer).

**Dimensions: L/W/H
91/ 6/ 63.2 mm
Tension-clamp connection / Nominal cross-section 1.5 mm²
Protection degree: IP 20**

**Input
0.5...20 mA
Output
Double switching output PNP/ 50 mA per channel**

**Adjustable via potentiometer
Switching hysteresis of input 1 %
Step response time < 250 us (10...90 %)
Temperature coefficient < 250 ppm K
Auxiliary power 24 V DC +/- 20 %
Ambient temperature range 0°C...+50 °C
Approvals cURus, CSA**

**Type
SC 0-20MA MCZ**

**Trip amplifier for monitoring a 0...20 mA standard signal with two switching outputs
Trip amplifier in 6 mm width for analogue 0...20 mA standard signals with two PNP-transistor switch outputs for monitoring an upper and lower threshold (adjustable via potentiometer).**

MCZ SC 0-20MA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS	Conform
UL File Number Search	E141197

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
User Documentation	Instruction sheet

MCZ SC 0-20mA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Connection diagram

