


DK NAND 35 24VDC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Logic functions AND, NAND, OR and NOR in modular terminal format with a rated cross-section of 4 mm². They each have five inputs which are fed – with logic gating – via a 24 V/20 mA PNP output. The logic components can be used for many applications involving the coupling of digital sensor/actuator signals with automation devices.

General ordering data

General ordering data	
Version	Function component
Order No.	8248320000
Type	DK NAND 35 24VDC
GTIN (EAN)	4008190406707
Qty.	5 pc(s).

DK NAND 35 24VDC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	57 mm	Height (inches)	2.244 inch
Length	65 mm	Length (inches)	2.559 inch
Net weight	29.2 g	Width	12 mm
Width (inches)	0.472 inch		

Temperatures

Storage temperature	-40 °C...60 °C	Operating temperature	0 °C...50 °C
Humidity	40 °C / 93 % rel. humidity, no condensation		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Current consumption	< 5 mA	Galvanic isolation	Without isolation
Humidity	40 °C / 93 % rel. humidity, no condensation	Input/Output	Logic module
Open sides	right	Rail	TS 35
Type of connection	Screw connection	Voltage supply	24...30 V DC

Insulation coordination

Insulation voltage input or output/rail	4 kV _{eff}	Standards	DIN EN 50178
---	---------------------	-----------	--------------

Input

Input current	Approx. 1.5 mA per input (24 V)	Number of inputs	5
Pulse duration	≥ 50 µs	Rated input level	24 V DC= High, 0 V = Low
Rated voltage (text)	Max. 30 V		

Output

Load impedance current	≤ 600 Ω	Number of outputs	1
Output current	max. 20 mA	Output level	PNP, Ub-1.8 V
Switching thresholds	High <15 V, low < 9 V		

Connection data

Type of connection	Screw connection	Clamping range, rated connection	4 mm ²
Clamping range, min.	0.5 mm ²	Clamping range, max.	4 mm ²

Classifications

ETIM 6.0	EC001417	ETIM 7.0	EC001417
ECLASS 9.0	27-24-22-16	ECLASS 9.1	27-21-92-90
ECLASS 10.0	27-24-22-16	ECLASS 11.0	27-24-22-16

DK NAND 35 24VDC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of
Conformity

[Declaration of Conformity.pdf](#)

Engineering Data

[EPLAN, WSCAD](#)

DK NAND 35 24VDC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

