

RPW705730**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Similar to illustration

General ordering data

Version	RIDERSERIES RPW, Relay, Number of contacts: 3, CO contact AgCdO, Rated control voltage: 230 V AC, Continuous current: 16 A, Plug-in connection
Order No.	8690810000
Type	RPW705730
GTIN (EAN)	4032248361397
Qty.	25 pc(s).
Delivery status	Discontinued
Available until	2018-12-31
Alternative product	1219440000

Creation date March 29, 2021 11:08:42 PM CEST

RPW705730

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	48.5 mm	Depth (inches)	1.909 inch
Height	35.5 mm	Height (inches)	1.398 inch
Net weight	93.88 g	Width	38.5 mm
Width (inches)	1.516 inch		

Temperatures

Storage temperature	-40 °C...50 °C	Operating temperature	-45 °C...50 °C
Humidity	40 °C / 93 % rel. humidity, no condensation		

Rated data UL

Certificate No. (cURus)	E224238
-------------------------	---------

Control side

Coil resistance	7500 $\Omega \pm 10\%$	Power rating	2.8 VA
Pull-in/drop-out voltage, typ.	184 V / 69 V AC	Rated control voltage	230 V AC
Rated current AC	11.7 mA		

Load side

AC switching capacity (resistive), max.	6000 VA	Continuous current	16 A
DC switching capacity (resistive), max.	384 W @ 24 V	Inrush current	40 A / 20 ms
Max. switching frequency at rated load	0.1 Hz	Max. switching voltage, AC	440 V
Min. switching power	100 mA @ 24 V	Rated switching voltage	400 V AC
Switch-off delay	≤ 10 ms	Switch-on delay	≤ 15 ms

Contact data

Contact type	3 CO contact (AgCdO)	Mechanical service life	20 x 10 ⁶ switching cycles
--------------	----------------------	-------------------------	---------------------------------------

General data

Version	Housing with mounting angle	Rail	TS 35
Test button	No	Mechanical switch position indicator	Yes
Colour	Transparent	UL 94 flammability rating	V-2

Insulation coordination

Creepage and clearance distance input – output	≥ 4 mm	Dielectric strength of neighbouring contacts	2.5 kV _{eff} / 1 Min.
Dielectric strength of open contact	1.5 kV _{eff} / 1 min.	Dielectric strength, Input/Output	2.5 kV _{eff} / 1 Min.
Impulse withstand voltage	4 kV (1.2/50 μ s)	Insulating material group	IIIa
Pollution severity	2	Protection degree	IP20
Rated voltage	250 V	Surge voltage category	III

Further details of approvals / standards

Standards	IEC 61810-1, UL508	Certificate No. (CSA)	249409-2426937
Certificate No. (VDE)	40013243	Certificate No. (cURus)	E224238

RPW705730**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Connection data**

Wire connection method	Plug-in connection
------------------------	--------------------

Classifications

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ECLASS 9.0	27-37-16-01	ECLASS 9.1	27-37-16-01
ECLASS 10.0	27-37-16-01	ECLASS 11.0	27-37-16-01

Approvals

Approvals



ROHS	Conform
UL File Number Search	E224238

Downloads

Approval/Certificate/Document of Conformity	DE_PA5600_160401_004.pdf
Engineering Data	EPLAN_WSCAD


RPW705730

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany


www.weidmueller.com

Drawings


Graph



Graph



Graph



RPW705730
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com
Drawings
Miscellaneous

	RPW				
Type					
RIDER PoWer					
Type of contact					
2 2CO					
7 3CP					
Type of construction					
0 Without test button					
3 With test button					
Housing					
2 Cap without lug, 4,8mm Faston					
5 Cap with lug, 6,3mm Faston					
					Coil voltage
					006 6 V DC
					012 12 V DC
					024 24 V DC
					048 48 V DC
					060 60 V DC
					110 110 V DC
					506 6 V AC
					512 12 V AC
					524 24 V AC
					548 48 V AC
					615 115 V AC
					730 230 V AC

Type codes