


**RRD3211B0****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Similar to illustration

**General ordering data**

|            |                                                                                                                                                                      |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | RIDERSERIES RRD, Relay, Number of contacts: 3, CO contact with test button AgNi 90/10, Rated control voltage: 110 V DC, Continuous current: 10 A, Plug-in connection |
| Order No.  | <a href="#">8797640000</a>                                                                                                                                           |
| Type       | RRD3211B0                                                                                                                                                            |
| GTIN (EAN) | 4032248491667                                                                                                                                                        |
| Qty.       | 25 pc(s).                                                                                                                                                            |

Creation date March 29, 2021 11:18:09 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## RRD3211B0

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 57 mm      | Depth (inches)  | 2.244 inch |
| Height         | 35.5 mm    | Height (inches) | 1.398 inch |
| Net weight     | 82.68 g    | Width           | 35.5 mm    |
| Width (inches) | 1.398 inch |                 |            |

## Temperatures

|                     |                                                |                       |                |
|---------------------|------------------------------------------------|-----------------------|----------------|
| Storage temperature | -40 °C...60 °C                                 | Operating temperature | -40 °C...60 °C |
| Humidity            | 40 °C / 93 % rel. humidity,<br>no condensation |                       |                |

## Rated data UL

|                         |         |
|-------------------------|---------|
| Certificate No. (cURus) | E224238 |
|-------------------------|---------|

## Control side

|                       |                         |                                |                    |
|-----------------------|-------------------------|--------------------------------|--------------------|
| Coil resistance       | 10000 $\Omega \pm 12\%$ | Power rating                   | 1.2 W              |
| Protective circuit    | Free-wheeling diode     | Pull-in/drop-out voltage, typ. | 82.5 V / 11.5 V DC |
| Rated control voltage | 110 V DC                | Rated current DC               | 11 mA              |

## Load side

|                                         |                                         |                            |              |
|-----------------------------------------|-----------------------------------------|----------------------------|--------------|
| AC switching capacity (resistive), max. | 2500 VA                                 | Continuous current         | 10 A         |
| DC switching capacity (resistive), max. | 240 W @ 24 V                            | Inrush current             | 20 A / 20 ms |
| Max. switching frequency at rated load  | 0.1 Hz                                  | Max. switching voltage, AC | 400 V        |
| Min. switching power                    | 1 mA @ 24 V, 10 mA @ 12 V, 100 mA @ 5 V | Rated switching voltage    | 250 V AC     |
| Switch-off delay                        | $\leq 10$ ms                            | Switch-on delay            | $\leq 15$ ms |

## Contact data

|              |                                            |                         |                                       |
|--------------|--------------------------------------------|-------------------------|---------------------------------------|
| Contact type | 3 CO contact with test button (AgNi 90/10) | Mechanical service life | 20 x 10 <sup>6</sup> switching cycles |
|--------------|--------------------------------------------|-------------------------|---------------------------------------|

## General data

|             |                |                                      |     |
|-------------|----------------|--------------------------------------|-----|
| Test button | yes (lockable) | Mechanical switch position indicator | Yes |
| Colour      | Transparent    | UL 94 flammability rating            | V-2 |

## Insulation coordination

|                                                |                                |                                              |                                |
|------------------------------------------------|--------------------------------|----------------------------------------------|--------------------------------|
| Creepage and clearance distance input – output | $\leq 3$ mm                    | Dielectric strength of neighbouring contacts | 2.5 kV <sub>eff</sub> / 1 Min. |
| Dielectric strength of open contact            | 1.5 kV <sub>eff</sub> / 1 min. | Dielectric strength, Input/Output            | 2.5 kV <sub>eff</sub> / 1 Min. |
| Impulse withstand voltage                      | 2.5 kV (1.2/50 $\mu$ s)        | Insulating material group                    | IIIa                           |
| Pollution severity                             | 2                              | Protection degree                            | IP20                           |
| Rated voltage                                  | 250 V                          | Surge voltage category                       | III                            |

## Further details of approvals / standards

|                       |                    |                         |                |
|-----------------------|--------------------|-------------------------|----------------|
| Standards             | IEC 61810-1, UL508 | Certificate No. (CSA)   | 249409-2426937 |
| Certificate No. (VDE) | 40011757           | Certificate No. (cURus) | E224238        |

**RRD3211B0****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Connection data**

|                        |                    |
|------------------------|--------------------|
| Wire connection method | Plug-in connection |
|------------------------|--------------------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001437    | ETIM 7.0    | EC001437    |
| ECLASS 9.0  | 27-37-16-01 | ECLASS 9.1  | 27-37-16-01 |
| ECLASS 10.0 | 27-37-16-01 | ECLASS 11.0 | 27-37-16-01 |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E224238 |

**Downloads**

|                                             |                                                                         |
|---------------------------------------------|-------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EU Konformitätserklärung / EU Declaration of Conformity</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                            |

## RRD3211B0


**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)


## Drawings

### Wiring diagram


Circuit diagram  
View of connections




### Graph



### Graph



### Graph



## RRD3211B0

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Drawings

## Miscellaneous

|                                                                                                                                                                                       |     |  |  |                     |                            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|--|--|---------------------|----------------------------|
|                                                                                                                                                                                       | RRD |  |  |                     |                            |
| <b>Type</b><br>RIDER Round                                                                                                                                                            |     |  |  |                     |                            |
| <b>Type of contact</b><br>2 2CO, 8-pole<br>3 3CO, 11-pole                                                                                                                             |     |  |  |                     |                            |
| <b>Contact material</b><br>2 AgNi 90/10                                                                                                                                               |     |  |  |                     |                            |
| <b>Type of construction</b><br>1 DC coil with test button<br>3 DC coil with test button and bi-polar LED<br>6 AC coil with test button<br>8 AC coil with test button and bi-polar LED |     |  |  |                     |                            |
|                                                                                                                                                                                       |     |  |  | <b>Coil voltage</b> |                            |
|                                                                                                                                                                                       |     |  |  | 006                 | 6 V DC                     |
|                                                                                                                                                                                       |     |  |  | 012                 | 12 V DC                    |
|                                                                                                                                                                                       |     |  |  | 024                 | 24 V DC                    |
|                                                                                                                                                                                       |     |  |  | 048                 | 48 V DC                    |
|                                                                                                                                                                                       |     |  |  | 060                 | 60 V DC                    |
|                                                                                                                                                                                       |     |  |  | 110                 | 110 V DC                   |
|                                                                                                                                                                                       |     |  |  | 220                 | 220 V DC                   |
|                                                                                                                                                                                       |     |  |  | 0C4                 | 24 V DC+ free wheel diode  |
|                                                                                                                                                                                       |     |  |  | 0E8                 | 48 V DC+ free wheel diode  |
|                                                                                                                                                                                       |     |  |  | 0G0                 | 60 V DC+ free wheel diode  |
|                                                                                                                                                                                       |     |  |  | 1B0                 | 110 V DC+ free wheel diode |
|                                                                                                                                                                                       |     |  |  | 2C0                 | 220 V DC+ free wheel diode |
|                                                                                                                                                                                       |     |  |  | 006                 | 6 V AC                     |
|                                                                                                                                                                                       |     |  |  | 012                 | 12 V AC                    |
|                                                                                                                                                                                       |     |  |  | 024                 | 24 V AC                    |
|                                                                                                                                                                                       |     |  |  | 048                 | 48 V AC                    |
|                                                                                                                                                                                       |     |  |  | 115                 | 115 V AC                   |
|                                                                                                                                                                                       |     |  |  | 230                 | 230 V AC                   |

Type codes