

RCLKITZ 230VAC 2CO LED**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Similar to illustration

General ordering data

Version	RIDERSERIES RCL, Relay module, Number of contacts: 2, CO contact AgNi 90/10, Rated control voltage: 230 V AC, Continuous current: 8 A, Tension-clamp connection
Order No.	8798670000
Type	RCLKITZ 230VAC 2CO LED
GTIN (EAN)	4032248494293
Qty.	10 pc(s).
Relevant base	8783930000
Relevant relay	4058630000

Creation date March 29, 2021 11:18:32 PM CEST

RCLKITZ 230VAC 2CO LED

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	69 mm	Depth (inches)	2.717 inch
Height	97 mm	Height (inches)	3.819 inch
Net weight	61.6 g	Width	16 mm
Width (inches)	0.63 inch		

Temperatures

Storage temperature	-40 °C...70 °C	Operating temperature	-40 °C...70 °C
Humidity	40 °C / 93 % rel. humidity, no condensation		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Control side

Coil resistance	32500 $\Omega \pm 15\%$	Power rating	0.75 VA
Protective circuit	Free-wheeling diode	Pull-in/drop-out voltage, typ.	172.5 V / 34.5 V AC
Rated control voltage	230 V AC	Rated current AC	3.2 mA
Status indicator	red LED		

Load side

AC switching capacity (resistive), max.	4000 VA	Continuous current	8 A
DC switching capacity (resistive), max.	384 W @ 24 V	Inrush current	15 A / 4 s
Max. switching voltage, AC	240 V	Min. switching power	1 mA @ 24 V, 10 mA @ 12 V, 100 mA @ 5 V
Rated switching voltage	250 V AC	Switch-off delay	≤ 6 ms
Switch-on delay	≤ 10 ms		

Contact data

Contact type	2 CO contact (AgNi 90/10)	Mechanical service life	AC coil 5×10^6 switching cycles
--------------	---------------------------	-------------------------	--

General data

Rail	TS 35	Test button	No
Mechanical switch position indicator	No	Colour	black
UL 94 flammability rating	V-2		

Insulation coordination

Dielectric strength, Input/Output	5 kV _{eff} / 1min	Pollution severity	2
Protection degree	IP20		

Further details of approvals / standards

Standards	DIN EN 50178	Certificate no. (CSA) relay	249409-2426937
Certificate no. (cURus) relay	E224238	Certificate no. (cURus) base	E223759

RCLKITZ 230VAC 2CO LED**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Connection data**

Wire connection method	Tension-clamp connection	Clamping range, rated connection	2.5 mm ²
Clamping range, min.	0.5 mm ²	Clamping range, max.	1.5 mm ²
Blade size	0.4 x 2.5 mm		

Classifications

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ECLASS 9.0	27-37-16-01	ECLASS 9.1	27-37-16-01
ECLASS 10.0	27-37-16-01	ECLASS 11.0	27-37-16-01

Approvals

Approvals



ROHS

Conform

DownloadsApproval/Certificate/Document of
Conformity[EU Konformitätserklärung / EU Declaration of Conformity](#)

Engineering Data

[EPLAN, WSCAD](#)


RCLKITZ 230VAC 2CO LED

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Wiring diagram



Graph

