

**IE-FM5D2UE0010MST0ST0X****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Assembled IE cables, FO breakout cable, multimode, SC duplex - SC duplex, black, Core diameter 50 µm

**General ordering data**

|            |                                                |
|------------|------------------------------------------------|
| Version    | Dragline cable, ST, ST IP 20, 50 µm, PUR, 10 m |
| Order No.  | <a href="#">8876450100</a>                     |
| Type       | IE-FM5D2UE0010MST0ST0X                         |
| GTIN (EAN) | 4032248610020                                  |
| Qty.       | 1 pc(s).                                       |

## IE-FM5D2UE0010MST0ST0X

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |       |                 |              |
|------------|-------|-----------------|--------------|
| Length     | 10 m  | Length (inches) | 393.701 inch |
| Net weight | 140 g |                 |              |

## Temperatures

|                          |                |                       |                |
|--------------------------|----------------|-----------------------|----------------|
| Storage temperature      | -40 °C...80 °C | Operating temperature | -40 °C...80 °C |
| Installation temperature | -20 °C...60 °C |                       |                |

## General standards

|                    |             |
|--------------------|-------------|
| Connector standard | IEC 61754-2 |
|--------------------|-------------|

## Standards

|                    |             |
|--------------------|-------------|
| Connector standard | IEC 61754-2 |
|--------------------|-------------|

## Fibre-optic

|                           |                                                |                |                                             |
|---------------------------|------------------------------------------------|----------------|---------------------------------------------|
| Attenuation               | 2.3 dB/km at 850 nm, &le; 0.5 dB/km at 1300 nm | Bandwidth      | 500 MHz*km at 850 nm, 500 MHz*km at 1300 nm |
| Fibre type                | GOF, Multimode, OM2                            | Insertion loss | ≤ 0.4 dB                                    |
| Return loss (attenuation) | ≥ 30 dB                                        |                |                                             |

## Cable structure

|                 |                    |                  |        |
|-----------------|--------------------|------------------|--------|
| Cable layout    | Break-out dragline | Core diameter    | 50 µm  |
| Material sheath | PUR                | Primary coating  | 245 µm |
| Sheath diameter | 6 mm               | Sheathing colour | black  |

## Mechanical and material properties of cable

|                                |         |                                 |       |
|--------------------------------|---------|---------------------------------|-------|
| Bending cycles                 | 100,000 | Halogen                         | No    |
| Min. bending radius, once only | 25 mm   | Min. bending radius, repetitive | 77 mm |

## Plug, left

|                |    |
|----------------|----|
| Connector left | ST |
|----------------|----|

## Plug, right

|                 |          |
|-----------------|----------|
| Connector right | ST IP 20 |
|-----------------|----------|

## plug

|                |    |                 |          |
|----------------|----|-----------------|----------|
| Connector left | ST | Connector right | ST IP 20 |
|----------------|----|-----------------|----------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002607    | ETIM 7.0    | EC002607    |
| ECLASS 9.0  | 27-06-10-03 | ECLASS 9.1  | 27-06-10-03 |
| ECLASS 10.0 | 27-06-10-03 | ECLASS 11.0 | 27-06-10-03 |

## IE-FM5D2UE0010MST0ST0X

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                                                    |
|--------------------|--------------------------------------------------------------------|
| Engineering Data   | <a href="#">WSCAD</a>                                              |
| User Documentation | <a href="#">MAN IE GUIDE DE</a><br><a href="#">MAN IE GUIDE EN</a> |

## IE-FM5D2UE0010MST0ST0X

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Detailed drawing

