

IE-C5ES8UG0013A40A40-E

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Industrial Ethernet connection technology by Weidmüller offers the optimal solution for the infrastructure of your machine, system or factory. All connection technology is available from one source.

The benefits for you:

- IEC-standardised connectors, in the variants 1, 4, 5, 6 and 14
- consistently Cat. 6_A with **STEADYTEC**® technology
- in IP20 and IP67
- all relevant industrial connections: RJ45, SC, ...
- comprehensive range of accessories

General ordering data

| | |
|------------|---|
| Version | System cable, RJ45 IP 20, RJ45 IP 20, Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B), PUR, 1.3 m |
| Order No. | 8935660013 |
| Type | IE-C5ES8UG0013A40A40-E |
| GTIN (EAN) | 4050118676341 |
| Qty. | 1 pc(s). |

Creation date April 16, 2021 9:19:19 AM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

IE-C5ES8UG0013A40A40-E

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|----------|-----------------|-------------|
| Length | 1.3 m | Length (inches) | 51.181 inch |
| Net weight | 63.988 g | | |

Temperatures

| | | | |
|--------------------------|----------------|-----------------------|----------------|
| Storage temperature | -40 °C...80 °C | Operating temperature | -40 °C...80 °C |
| Installation temperature | -10 °C...60 °C | | |

Environmental Product Compliance

| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

Cable specific standards

| | | | |
|------------------------|---------------------------|--|---------------------------------------|
| Corrosiveness of fumes | to IEC 60754-2 | Generic communication cable facilities | ISO / IEC 11801:2002, EN 50173-1:2007 |
| Standard, assembly | UL-Style 20963 (80°C/30V) | | |

Cable structure

| | | | |
|---------------------------|---|---------------------------------------|--|
| Arrangement of wire cores | Twisted pair | Colour sequence or wires - wire pairs | white - blue, white - orange, white - green, white - brown |
| Complete shielding | Aluminium foil, Shielding braid made from copper wiring | Cross-section | 4*2*AWG 26/7 - 4*2*0.128 mm ² |
| Insulation | PE | Insulation cross-section | 1 mm |
| Material sheath | PUR | Number of wires | 8 |
| Sheath diameter, max. | 6.1 mm | Sheath diameter, min. | 5.7 mm |
| Sheathing colour | green (RAL 6018) | Shielding | SF/UTP |
| Shielding braid thickness | 0.1 mm | Standard designations | SF/UTP, IE-7IC4x2xAWG23/1-PUR 02YSC11Y PIMF |
| Strands | 7 | Wire material | Stranded tin-plated copper wire |

Electrical properties of cable

| | | | |
|--------------------------------|---------------------|-------------------------|---|
| Capacity at 1 kHz | 50 nF/km | Category | Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B) |
| Characteristic impedance | 100 ± 5 Ω at 100MHz | Deviation | 25 ns/100m |
| Loop resistance | 290 Ω/km | Signal propagation time | 4.85 ns/m |
| Test voltage: wire-wire-shield | 700 V AC | | |

Mechanical and material properties of cable

| | | | |
|---------------------------------|--|--------------------------------|----------------------------------|
| Abrasion resistance | very good | Corrosiveness of fumes | to IEC 60754-2 |
| Halogen | halogen-free, according to IEC 60754-2 | Min. bending radius, once only | 5 x cable diameter |
| Min. bending radius, repetitive | 10 x cable diameter | Resistance to oils | in accordance with IEC 60811-2-1 |
| Resistance to spread of flame | in accordance with IEC 60332-1 | Silicone-free | Yes |
| UV-resistant | Yes | | |

Creation date April 16, 2021 9:19:19 AM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

2

Data sheet

IE-C5ES8UG0013A40A40-E

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

plug

| | | | |
|----------------|------------|-----------------|------------|
| Connector left | RJ45 IP 20 | Connector right | RJ45 IP 20 |
|----------------|------------|-----------------|------------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002599 | ETIM 7.0 | EC002599 |
| ECLASS 9.0 | 27-06-03-08 | ECLASS 9.1 | 27-06-03-08 |
| ECLASS 10.0 | 27-06-03-08 | ECLASS 11.0 | 27-06-03-08 |

Downloads

| | |
|--------------------|--|
| Engineering Data | STEP |
| Brochure/Catalogue | Catalogues in PDF-format |