

IE-FM5D2UE-MW**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Bulk stock, FO cable, glass fibre

General ordering data

Version	Dragline cable, 50 µm, PUR, Products sold by meter, from 50 m
Order No.	8946000000
Type	IE-FM5D2UE-MW
GTIN (EAN)	4032248733736
Qty.	1 m
Delivery status	This article will no longer be available in the future.
Available until	2021-01-31

Creation date March 29, 2021 11:50:56 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-FM5D2UE-MW

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	26 g
------------	------

Temperatures

Storage temperature	-40 °C...80 °C	Operating temperature	-40 °C...80 °C
Installation temperature	-20 °C...60 °C		

Fibre-optic

Attenuation	2.3 dB/km at 850 nm, ≤ 0.5 dB/km at 1300 nm	Bandwidth	500 MHz*km at 850 nm, 500 MHz*km at 1300 nm
Fibre type	GOF, Multimode, OM2		

Cable structure

Cable layout	Break-out dragline	Core diameter	50 µm
Material sheath	PUR	Primary coating	245 µm
Sheath diameter	6 mm	Sheathing colour	black

Mechanical and material properties of cable

Bending cycles	100,000	Halogen	No
Min. bending radius, once only	25 mm	Min. bending radius, repetitive	77 mm

Classifications

ETIM 6.0	EC000034	ETIM 7.0	EC000034
ECLASS 9.0	27-06-18-03	ECLASS 9.1	27-06-90-90
ECLASS 10.0	27-06-18-03	ECLASS 11.0	27-06-18-03

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	WSCAD
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN

IE-FM5D2UE-MW

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

Detailed drawing

