

IE-C7BS8UG-MW**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Bulk stock, copper cable, rigid, 4 x 2 x AWG 23/1, Cat. 7,
green

General ordering data

Version	Installation cable, Cat.7 (ISO/IEC 11801), PUR, Products sold by meter, from 110 m
Order No.	8955350000
Type	IE-C7BS8UG-MW
GTIN (EAN)	4032248753185
Qty.	1 m
Delivery status	This article will no longer be available in the future.
Available until	2020-10-31

Creation date March 30, 2021 12:01:35 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-C7BS8UG-MW**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	6 g
------------	-----

Temperatures

Storage temperature	-40 °C...80 °C	Operating temperature	-40 °C...80 °C
Installation temperature	-15 °C...60 °C		

Technical specifications for cable

Halogen	halogen-free, according to IEC 60754-2	Insulation	PE
Number of wires	8	Resistance to oils	in accordance with IEC 60811-2-1
Resistance to spread of flame	in accordance with IEC 60332-1	Sheathing colour	green (RAL 6018)
Test voltage: wire-wire-shield	700 V AC		

Cable specific standards

Corrosiveness of fumes	to IEC 60754-2	Generic communication cable facilities	ISO / IEC 11801:2002, EN 50173-1:2007
------------------------	----------------	--	---------------------------------------

Electrical properties

Insulation strength	5000 MΩ
---------------------	---------

Standards

Corrosiveness of fumes	to IEC 60754-2	Generic communication cable facilities	ISO / IEC 11801:2002, EN 50173-1:2007
------------------------	----------------	--	---------------------------------------

Cable structure

Arrangement of wire cores	Twisted pair	Colour sequence or wires - wire pairs	white - blue, white - orange, white - green, white - brown
Complete shielding	Shielding braid made from copper wiring	Cross-section	4*2*AWG 23/1 - 4*2*0.255 mm ²
Insulation	PE	Insulation cross-section	1.4 mm
Material sheath	PUR	Number of wires	8
Sheath diameter, max.	8.4 mm	Sheath diameter, min.	8 mm
Sheathing colour	green (RAL 6018)	Shielding	S/FTP
Shielding braid thickness	0.1 mm	Standard designations	IE-7IC4x2xAWG23/1-PUR 02YSC11Y PIMF, S/FTP
Strands	1	Wire material	Non-insulated copper wire
Wire pair shielding	Aluminium foil		

Electrical properties of cable

Capacity at 1 kHz	45 nF/km	Category	Cat.7 (ISO/IEC 11801)
Characteristic impedance	100 ± 5 Ω at 100MHz	Deviation	5 ns/100m
Insulation strength	5000 MΩ	Loop resistance	150 Ω/km
Signal propagation time	4.25 ns/m	Test voltage: wire-wire-shield	700 V AC

IE-C7BS8UG-MW**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Mechanical and material properties of cable**

Abrasion resistance	very good	Colour	green
Corrosiveness of fumes	to IEC 60754-2	Halogen	halogen-free, according to IEC 60754-2
Min. bending radius, once only	5 x cable diameter	Min. bending radius, repetitive	10 x cable diameter
Resistance to oils	in accordance with IEC 60811-2-1	Resistance to spread of flame	in accordance with IEC 60332-1
Silicone-free	Yes	UV-resistant	Yes

Classifications

ETIM 6.0	EC000830	ETIM 7.0	EC003249
ECLASS 9.0	27-06-18-05	ECLASS 9.1	27-06-90-90
ECLASS 10.0	27-06-18-01	ECLASS 11.0	27-06-18-01

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN
--------------------	--

IE-C7BS8UG-MW

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Detailed drawing

