

ALPHA 160, wall-mounted cabinet, with distribution board panel,
IP43, safety class 2, H: 650 mm, W: 300 mm, D: 140 mm, RAL 9016



Surface processing	powder-coated
Protection class	
Protection class IP	IP43
Suitability for interaction / lightning protection	Yes
Suitability for use / for outside use	No
Appearance	
RAL color number	RAL 9016
Product component	
• cable entry	Yes
• Mounting plate	No
Product extension / optional / Side-by-side mounting	No
Mechanical Design	
Height	650 mm
Width	300 mm
Depth	140 mm
Installation depth	140 mm
Net weight	7.76 kg
Material / of the enclosure	Steel

General Product Approval	Declaration of Conformity	Test Certificates
	 EG-Konf.	sonstig Typprüfbescheinigung/Werkszeugnis spezielle Prüfbescheinigungen sonstig

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8GK1052-2KK11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8GK1052-2KK11/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK1052-2KK11

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

