

ALPHA 400, wall-mounted cabinet, IP43, safety class 2,
H: 650 mm, W: 800 mm, D: 210 mm, RAL 9016



Surface processing		powder-coated
Protection class		
Protection class IP		IP43
Suitability for interaction / lightning protection		Yes
Suitability for use / for outside use		No
Appearance		
RAL color number		RAL 9016
Product component		
• cable entry		Yes
• Mounting plate		No
Product extension / optional / Side-by-side mounting		Yes
Mechanical Design		
Height	mm	650
Width	mm	800
Depth	mm	210
Installation depth	mm	210
Net weight	kg	19
Material / of the enclosure		Steel

General Product Approval	Declaration of Conformity	Test Certificates
--------------------------	---------------------------	-------------------

[sonstig](#)



[spezielle
Prüfbescheinigung
n](#)

[Typprüfbescheinigung/
Werkszeugnis](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8GK1132-2KK32>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8GK1132-2KK32/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK1132-2KK32

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

