



8HP WITH 3VL CIRCUIT-BREAKER 250A,
TM-RELEASE, 4-POLE

Similar to image

Technical data:

Number of poles		4
Depth	mm	239
Height	mm	614
Width	mm	307
Product function		
• thermoprotection		No
• ground-fault protection		No
Adjustable response current		
• of the current-dependent overload release	A	1,200 ... 2,500
Mounting type / series installation		No
Operating current / rated value	A	250
Breaking capacity current / at 400 V	kA	55
Operating voltage / at 50 Hz / with AC / rated value	V	415

Certificates/approvals:

General Product Approval	Declaration of Conformity	Test Certificates	
 GOST	 EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8HP2203-3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8HP2203-3/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8HP2203-3

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Aug 12, 2014