



THERMOSTAT FOR CUBICLE-HEATER UNITE AC/DC 110
-265V,
50/60HZ

Similar to image

General details:		
product brand name		SIVACON
Product designation		thermostat
mounting position		any
Width	mm	50
Height	mm	67
Depth	mm	38
Net weight	kg	0.1
Operating current / Rated value	A	10
Type of voltage		AC
Mounting type		terminal mounting
Operating voltage / Rated value	V	230
Adjustable temperature	°C	5 ... 60
Product component		
• hygrostat		No
• digital display		No
Design of the switching function		CO contact
Material / of the enclosure		plastic
Switching difference of the temperature	K	5

Mechanical service life (switching cycles) / typical		100,000
Inrush current / typical	A	6
Operating temperature	°C	-45 ... +65
Ambient temperature • during storage	°C	-45 ... +65
Relative humidity / Reference value	%	90
Reference code • acc. to DIN EN 61346-2 • acc. to DIN EN 81346-2		K K

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8MR2170-1A/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8MR2170-1A

last change:

Nov 3, 2014