



SMALL THERMOSTAT BREAK CONTACT,
20 TO 80 DEG. C KTO 01140 01159.0-00

Similar to image

General details:		
product brand name		SIVACON
mounting position		any
Width	mm	33
Height	mm	60
Depth	mm	43
Net weight	kg	0.04
Operating current / rated value	A	10
Type of voltage		AC
Mounting type		terminal mounting
Operating voltage / rated value	V	250
Adjustable temperature	°C	20 ... 80
Product component		
• hygostat		No
• digital display		No
Design of the switching function		NC contact
Material / of the enclosure		plastic
Mechanical operating cycles as operating time / typical		100,000
Inrush current / typical	A	10

Operating temperature	°C	-45 ... +80
Ambient temperature • during storage	°C	-45 ... +80
Relative humidity / reference value	%	90
Item designation • according to DIN EN 61346-2 • according to DIN EN 81346-2		K K

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8MR2170-1DA/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8MR2170-1DA

last change:

Jul 7, 2014