



NO CONTACT+NO CONTACT,
50DEGR.,122DEGR.F FTD011, 01164.0-00,

Similar to image

General details:		
product brand name		SIVACON
mounting position		any
Width	mm	63
Height	mm	47
Depth	mm	33
Net weight	kg	0.04
Operating current / rated value	A	10
Type of voltage		AC
Operating voltage / rated value	V	250
Material / of the enclosure		plastic
Cut-out temperature	°C	40
Mechanical operating cycles as operating time / typical		100,000
Inrush current / typical	A	10
Operating temperature	°C	-40 ... +80
Ambient temperature during storage	°C	-45 ... +80
Relative humidity / reference value	%	90
Item designation		

- according to DIN EN 61346-2
- according to DIN EN 81346-2

	K
	K

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8MR2172-1AB/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8MR2172-1AB

last change:

Jul 7, 2014