

230V, 20M3/H, IP55 FF018, 01821.0.00,

Model		
product brandname		SIVACON
General technical data		
Operating temperature / minimum	°C	-45
Protection class		
Protection class IP		kein Wert
Main circuit		
Operating voltage		
<ul style="list-style-type: none"> at AC / at 50 Hz / rated value / maximum 	V	230
<ul style="list-style-type: none"> at AC / at 60 Hz / rated value / maximum 	V	230
Appearance		
Color		grey
Mechanical Design		
Net weight	kg	1.2
Certificates		
Equipment marking		
<ul style="list-style-type: none"> acc. to DIN EN 61346-2 		E
<ul style="list-style-type: none"> acc. to DIN EN 81346-2 		E
General Product Approval		



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8MR2410-0DA>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8MR2410-0DA/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8MR2410-0DA

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

10/14/2016