



COOLING UNIT DOOR OR WALL MOUNTED COOLING CAPACITY 1550 W 230 V AC RAL 7035 400X950X233 MM (WXHxD) INTERBAL CYCLE IP 54 OUTSIDE CYCLE IP 34

Similar to image

General details:		
product brand name		SIVACON
Product designation		Cooling device
Voltage type / of operating voltage		AC
Height	mm	950
Width	mm	400
Depth	mm	233
Net weight	kg	38
Material		steel
Operating voltage		
• at 50 Hz / at AC / rated value / maximum	V	230
• at 60 Hz / at AC / rated value / maximum	V	230
Design of the control cabinet cooler		Air/air
Product component		
• thermostat		Yes
• Heating		No
Cooling capacity / at L35L35	W	1,550
Starting current	A	18
Operating current		

<ul style="list-style-type: none"> • for motor / maximum rated value 	A	5.3
<ul style="list-style-type: none"> • of the fuse link / rated value 	A	10
Design of the electrical connection		Connector, 4-pole
Operating pressure / maximum permissible	bar	25
Temperature		
<ul style="list-style-type: none"> • of the inner cooling circuit 	°C	20 ... 46
<ul style="list-style-type: none"> • of the outer cooling circuit 	°C	20 ... 58
A-rated acoustic power level / maximum	dB	65
Item designation		
<ul style="list-style-type: none"> • according to DIN EN 61346-2 		E
<ul style="list-style-type: none"> • according to DIN EN 81346-2 		E

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8MR6423-5SK15/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8MR6423-5SK15

last change:

Jun 16, 2014