

Through-type terminal thermoplast Screw terminal on both sides
Terminal block 10-pole, beige Without designation 65.5 mm, Sz. 4




Figure similar

Model	
Product brand name	ALPHA
Product designation	ALPHA FIX terminal blocks
Design of terminal / Terminal levels internally linked	No
General technical data	
Terminal contact spacing	65.5 mm
Protection class	
Combustibility class acc. to UL 94	V2
Main circuit	
Operating voltage / rated value	800 V
Operating current / rated value	32 A
Appearance	
Color	beige
Product details	
Product component / required / connection plate	No

Number	
Number of terminal levels	1
Number of terminal points / per terminal level	2

Connections	
Wire stripping length	11 mm
Connectable conductor cross-section	4 ... 4 mm ²
• stranded	4 ... 4 mm ²
• finely stranded	4 ... 4 mm ²
Tightening torque / with screw-type terminals	0.5 ... 0.5 N·m
Type of electrical connection	screw-type terminal
• 1	screw-type terminal
• 2	screw-type terminal
Position / of the terminal	lateral

Mechanical Design	
Height / with lowest-profile installation	26 mm
Length	41 mm
Mounting type	DIN rail 35 mm
Net weight	95.6 g
Material / of the insulating body	Thermoplast

Environmental conditions	
Ambient temperature	-25 ... +55 °C
• during operation	(no derating)

Certificates	
Design tested acc. to type of protection / EEx e	No

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval	other
 CSA	 UR	 EG-Konf.	 BUREAU VERITAS	Environmental Confirmations

Further information
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1011-0DG21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1011-0DG21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-0DG21

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>